



Part Number:	ID (D) / tolerance	Concentricity
905-R-Z-126-A31	126um + 1/-0um	1um
905-R-Z-127-A31	127um + 5/-0um	5um
905-R-Z-144-A31	144um + 5/-0um	5um
905-R-Z-225-A31	225um + 5/-0um	10um
905-R-Z-235-A31	235um + 5/-0um	10um
905-R-Z-340-A31	340um + 10/-0um	20um
905-R-Z-450-A31	450um + 10/-0um	20um

- Part number in table are common sizes, example 905-R-Z-127-A31
 - Other ID sizes are available upon request. Specify exact ID size when ordering (available range 126um to 750um)

- Notes:
1. Dimensions are shown in millimeters
 2. Connector kit includes Ferrule Body with Nut, Crimp Ring Strain Relief Boot, and Dust Cover
 3. Change "R" designator in part number to "H" for Hex Nut

THIS DRAWING OR SPECIFICATION IS CONFIDENTIAL AND PROPRIETARY TO KIENTEC SYSTEMS, INC. AND MAY NOT BE REPRODUCED, OR DISCLOSED TO OTHERS WITHOUT THE WRITTEN CONSENT OF KIENTEC SYSTEMS, INC.

List of Materials:	
COMPONENT:	MATERIAL:
1 Ferrule	Zirconia
2 Coupling Nut	Brass
3 Dust Cover	Vinyl, Black
4 Strain Relief	Thermoplastic, Black

Kientec Systems, Inc.
 Stuart, FL 34994

SMA905 CONNECTOR

SIZE	DRAWN BY: C.A.K	DWG NO. 905-R-Z-xxx-A31	REV
	DATE: 7/1/09		
SCALE 2:1	SHEET 1 of 1		